

Titan 900S Scrub Dispensers



Titan 910S (10 Gates)



- Slots: 100 to 200
- Available as both RFID and non-RFID capable
- Weight: 500 Lbs.
- Dimensions(In):H78xW33xD30
- Slots per row: 10 or 20
- Rows: 10
- Slot dimensions:
 - 10/row= 8.5"W x 6.0"H x 10.8"D
 - 20/row= 4.3"W x 6.0"H x 10.8"D

Titan 912S (12 Gates)



- Slots: 120 to 240
- Available as both RFID and non-RFID capable
- Weight: 500 Lbs.
- Dimensions(In):H78xW33xD30
- Slots per row: 10 or 20
- Rows: 12
- Top 6 rows are 4.0" High
- Bottom 6 rows are 8.0" High
- Slot dimensions:
 - 10/row= 8.5"W x 6.0"H x 10.8"D
 - 20/row= 4.3"W x 6.0"H x 10.8"D

Titan 915S (15 Gates)



- Slots: 150-300
- Available as both RFID and non-RFID capable
- Weight: 500 Lbs.
- Dimensions(In):H78xW33xD30
- Slots per row: 10 or 20
- Rows: 12
- Top 6 rows are 4.0" High
- Bottom 6 rows are 8.0" High
- Slot dimensions:
 - 10/row= 8.5"W x 4.0"H x 10.8"D
 - 20/row= 4.3"W x 4.0"H x 10.8"D

900 Slim Technical Data

Titan versions: 10 gate, 12 gate, and 15 gate


Available in RFID and Non-RFID formats

Middleware Software ZCS Stargate

User Interface 10" touchscreen color industrial display

Card reader (according to customer specifications)

RFID UHF Technology Options ISO 18000 6c Class1 Generation 2



Two versions 10 or 20 slots per row

External structure material Powder coated sheet metal

Color of external structure Gray RAL 7035

Rotating cylinder material Polypropylene

Electrical connections :1 socket 110V/220V 0.5 KW

Network connections: 1 10/100/1000 Ethernet socket - WiFi – Cellular data chip

Machine dimensions W 35.6–D 31.7–H 77.0 Inches

Weight 500 Lbs.

Optional : 1 Lithium battery pack (range about 2 days)